FOOD & BEVERAGE

Generating a valuable water resource from milk evaporator condensate

New regulations meant a German dairy approached Ecolutia to help reduce its site discharge of wastewater. A modular treatment solution proved recovery of milk evaporator condensate to reduce discharge volumes but also create a new recoverable water source.



CLIENT	LOCATION	SERVICE	DURATION
Dairy and milk products manufacturing plant	Germany	Temporary: Condensate recovery	Two years

80 GPM	<5 ppm	5	12+ mth
PILOT PRODUCTION FLOW	PRODUCT WATER COD	STAGE TREATMENT TRAIN	PILOT EXTENDED

THE CHALLENGE

New discharge limits put production water under pressure

Incoming environmental regulations limited the wastewater discharge for a dairy manufacturing a variety of milk products. Encouraging results from a bench-scale study and discussions with Ecolutia led to the installation of a temporary service solution to recover milk evaporator condensate.

Proving the long-term case and economic viability of the solution was essential for compliance with the new regulations. However, recovery of the condensate needed to be on a modest footprint, sufficiently reduce wastewater discharge, adaptable for upgrades, suitable for future site

PROJECT SNAPSHOT

Feed source	Milk evaporator condensate (≤150 ppm COD)
Output quality	<5 ppm COD · <0.5 ppm NH_3
Flow delivered	80 GPM
Technologies	MMF, UF, BWRO, GAC, UV

growth plans, and a quality of condensate usable onsite.

THE SOLUTION

A modular solution, fine tuning each variable and configuration

With project goals set, Ecolutia deployed its mobile modular containerized and skid-mounted treatment systems. The small footprint and modular design made the systems ideal for the planned configuration work and adjustments to be tested by the project engineers — equipment could be reset swiftly between configurations to find the optimum setup while minimizing non-production periods.

- ✓ Two-stage pre-treatment — multi-media filtration, then ultrafiltration as an absolute barrier to larger organic molecules
- ✓ Reverse osmosis removing remaining dissolved organics and ammonia, with activated carbon polish for taste and odor
- ✓ Strict cleaning and sanitization regime controlling biological fouling from milk proteins and fats

TREATMENT FLOW PATH



THE RESULTS

Reuse proven — and the pilot extended beyond a year

Initial findings showed that recovered condensate could lower freshwater consumption and wastewater discharge costs, while reducing the dairy's environmental impact against the impending regulations.

The original installation was a pilot plant that proved the full-flow viability of the bench-scale study. This successful pilot led to an extension to test other complementary water treatment options — adding UV disinfection and chlorination trials for microbiological purity as well as firming up additional economics as part of the dairy's permanent long-term solution.

Talk to us about a similar project
info@ecolutia.com
www.ecolutia.com

CONTACT US

PLANNING A WATER REUSE PROJECT?

Full flow pilot to prove the concept.

info@ecolutia.com